

Datenblatt

080R265-G

Hängetaster, Fernbedienung, ungebohrt, gelb



Merkmale

Baureihe	Hängetaster, Fernbedienung 265x83 mm
Komponenten	Ungeborther
Artikel-Nr.	080R265-G
Beschreibung	Hängetaster, Fernbedienung, ungebohrt, gelb
Farbe	Giallo RAL1003 / Grigio RAL7035
Gewicht - gr	330,0
Zolltarifnummer	85381000
GTIN	8052878067670

Technische Daten

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1, IEC-EN60204-1
Operating temperatures	-35° ÷ +80°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK08 (IEC-EN62262)
Housing material	High impact grade thermoplastic polymer
Manufacturing process	Injection moulding
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	Torx T15 slotted head type
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Cable clamp screw	Tightening torque 1.5Nm (13.3 Lb-in) max.
Pendant fixing ring	Stainless steel AISI 304
Flexible cable gland	M20x1.5(enlarged model) suited for cable D.10÷14mm
Rated insulation voltage	Ui 300V - Uimp 2.5KV (IEC-EN60947-1)
Protection against electric shock	Class II (IEC-EN61140)
Combustion behaviour	HB (UL94)
Combustion behaviour	650°(IEC-EN60695-2-11)
Fitted for outdoor application	yes
Pushbutton and electrical contacts block	See 020 product range: 020 SM2 D.22mm
Warranty period	18 months

Technische Zeichnungen

