

## Scheda Dati

080R265-P1

Riippuohjain, kaukosäädin, 1 aukko , harmaa



## Caratteristiche

|                  |                                             |
|------------------|---------------------------------------------|
| Range            | Riippuohjainyksikkö, kaukosäädin 265x83 mm  |
| Componente       | 1 aukolla Ø 22                              |
| Code             | 080R265-P1                                  |
| Kuvaus           | Riippuohjain, kaukosäädin, 1 aukko , harmaa |
| Väriä            | Grigio RAL7016 / Grigio RAL7035             |
| Peso             | 300,0                                       |
| Tariffa doganale | 85381000                                    |
| GT               | 8052878067700                               |

## Dati tecnici

|                                          |                                                    |
|------------------------------------------|----------------------------------------------------|
| Approvals                                | CE                                                 |
| Compliance with standards                | IEC-ENC60947-1, IEC-EN60947-5-1, IEC-EN60204-1     |
| Operating temperatures                   | -35° ÷ +80°C                                       |
| Protection degree                        | IP66 - IP69 (IEC-EN60529)                          |
| Protection against impact                | IK08 (IEC-EN62262)                                 |
| Housing material                         | High impact grade thermoplastic polymer            |
| Manufacturing process                    | Injection moulding                                 |
| Gasket material                          | TPE thermoplastic elastomer                        |
| Screw material                           | Stainless steel AISI 304                           |
| Screw type                               | Torx T15 slotted head type                         |
| Tightening torque                        | 0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in)                       |
| Cable clamp screw                        | Tightening torque 1.5Nm (13.3 Lb-in) max.          |
| Pendant fixing ring                      | Stainless steel AISI 304                           |
| Flexible cable gland                     | M20x1.5(enlarged model) suited for cable D.10÷14mm |
| Rated insulation voltage                 | Ui 300V - Uimp 2.5KV (IEC-EN60947-1)               |
| Protection against electric shock        | Class II (IEC-EN61140)                             |
| Combustion behaviour                     | HB (UL94)                                          |
| Combustion behaviour                     | 650°(IEC-EN60695-2-11)                             |
| Fitted for outdoor application           | yes                                                |
| Pushbutton and electrical contacts block | See 020 product range: 020 SM2 D.22mm              |
| Warranty period                          | 18 months                                          |

## Disegni tecnici

