

Scheda Dati

080R265-P1

Boîtes à boutons pendantes, commande à distance, 1 trou, gris



Caratteristiche

Portée	Boîtes à boutons pendantes, commande à distance 265x83 mm
Componente	Avec 1 trou Ø 22
Code	080R265-P1
Désignation des marchandises	Boîtes à boutons pendantes, commande à distance, 1 trou, gris
Couleur	Grigio RAL7016 / Grigio RAL7035
Peso	300,0
Tariffa doganale	85381000
GTIN	8052878067700

Dati tecnici

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1, IEC-EN60204-1
Operating temperatures	-35° ÷ +80°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK08 (IEC-EN62262)
Housing material	High impact grade thermoplastic polymer
Manufacturing process	Injection moulding
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	Torx T15 slotted head type
Tightening torque	0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in)
Cable clamp screw	Tightening torque 1.5Nm (13.3 Lb-in) max.
Pendant fixing ring	Stainless steel AISI 304
Flexible cable gland	M20x1.5(enlarged model) suited for cable D.10÷14mm
Rated insulation voltage	Ui 300V - Uimp 2.5KV (IEC-EN60947-1)
Protection against electric shock	Class II (IEC-EN61140)
Combustion behaviour	HB (UL94)
Combustion behaviour	650°(IEC-EN60695-2-11)
Fitted for outdoor application	yes

Pushbutton and electrical contacts block

See 020 product range: 020 SM2 D.22mm

Warranty period

18 months

Disegni tecnici

