

Fiche technique

080R265-P7

Boîtes à boutons pendantes, commande à distance, 7 trous, gris



Caractéristiques

| | |
|-------------------------------------|--|
| Portée | Boîtes à boutons pendantes, commande à distance 265x83 mm |
| Composant | Avec 7 trous Ø 22 |
| Code | 080R265-P7 |
| Désignation des marchandises | Boîtes à boutons pendantes, commande à distance, 7 trous, gris |
| Couleur | Grigio RAL7016 / Grigio RAL7035 |
| Poids | 315,0 |
| Tarif douanier | 85381000 |
| GTIN | 8052878067687 |

Données techniques

| | |
|--|--|
| Approvals | CE |
| Compliance with standards | IEC-ENC60947-1, IEC-EN60947-5-1, IEC-EN60204-1 |
| Operating temperatures | -35° ÷ +80°C |
| Protection degree | IP66 - IP69 (IEC-EN60529) |
| Protection against impact | IK08 (IEC-EN62262) |
| Housing material | High impact grade thermoplastic polymer |
| Manufacturing process | Injection moulding |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Screw type | Torx T15 slotted head type |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Cable clamp screw | Tightening torque 1.5Nm (13.3 Lb-in) max. |
| Pendant fixing ring | Stainless steel AISI 304 |
| Flexible cable gland | M20x1.5(enlarged model) suited for cable D.10÷14mm |
| Rated insulation voltage | Ui 300V - Uimp 2.5KV (IEC-EN60947-1) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Combustion behaviour | HB (UL94) |
| Combustion behaviour | 650°(IEC-EN60695-2-11) |
| Fitted for outdoor application | yes |

Pushbutton and electrical contacts block

See 020 product range: 020 SM2 D.22mm

Warranty period

18 months
