# Datasheet

080RU140-GP1
Pendant push-button station, remote control, 1 hole, yellow, UL

## Features

| | |
|---|---|
| **Range** | Pendant push-button stations, remote control 140x83 mm |
| **components** | With 1 hole Ø 22 |
| **Code** | 080RU140-GP1 |
| **Description** | Pendant push-button station, remote control, 1 hole, yellow, UL |
| **Colour** | Giallo RAL1003 / Grigio RAL7035 |
| **Weight - gr** | 218.0 |
| **Customs Tariff** | 85381000 |
| **GTIN** | 8052878072216 |

## Datasheet

| | |
|---|---|
| **Approvals** | CE, UL, CSA |
| **Compliance with standards** | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| **Operating temperatures** | -35° ÷ +80°C |
| **Protection degree** | IP66 - IP69 (IEC-EN60529) |
| **Protection against impact** | IK08 (IEC-EN62262) |
| **Housing material** | High impact grade thermoplastic polymer |
| **Manufacturing process** | Injection moulding |
| **Gasket material** | TPE thermoplastic elastomer |
| **Screw material** | Stainless steel AISI 304 |
| **Screw type** | Torx T15 slotted head type |
| **Combustion behaviour** | V0 (UL94) |
| **Tightening torque** | 0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in) |
| **Cable clamp screw** | Tightening torque 1.5Nm (13.3 Lb-in) max. |
| **Pendant fixing ring** | Stainless steel AISI 304 |
| **Flexible cable gland** | M16x1.5 suitable for cable D.5÷10mm |
| **Rated insulation voltage** | Ui 300V - Uimp 2.5KV (IEC-EN60947-1) |
| **Protection against electric shock** | Class II (IEC-EN61140) |
| **Fitted for outdoor application** | yes |
| **Combustion behaviour** | 960°(IEC-EN60695-2-12) |
| **Pushbutton and electrical contacts block** | See 020 product range: 020 SM2 D.22mm |

| | |
|---|---|
| **Warranty period** | 18 months |

## Technical drawings