

## Datenblatt

080RU140-P1

Hängetaster, Fernbedienung, 1 Bohrung, grau, UL



## Merkmale

|                        |   |
|------------------------|---|
| <b>Baureihe</b>        | Hängetaster, Fernbedienung 140x83 mm            |
| <b>Komponenten</b>     | Mit 1 Bohrung Ø 22                              |
| <b>Artikel-Nr.</b>     | 080RU140-P1                                     |
| <b>Beschreibung</b>    | Hängetaster, Fernbedienung, 1 Bohrung, grau, UL |
| <b>Farbe</b>           | Grigio RAL7016 / Grigio RAL7035                 |
| <b>Gewicht - gr</b>    | 218,0   |
| <b>Zolltarifnummer</b> | 85381000  |
| <b>GTIN</b>            | 8052878072209                                   |

## Technische Daten

|   |  |
|---|--|
| <b>Approvals</b>                                | CE, UL, CSA                                      |
| <b>Compliance with standards</b>                | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| <b>Operating temperatures</b>                   | -35° ÷ +80°C                                     |
| <b>Protection degree</b>                        | IP66 - IP69 (IEC-EN60529)                        |
| <b>Protection against impact</b>                | IK08 (IEC-EN62262)                               |
| <b>Housing material</b>                         | High impact grade thermoplastic polymer          |
| <b>Manufacturing process</b>                    | Injection moulding                               |
| <b>Gasket material</b>                          | TPE thermoplastic elastomer                      |
| <b>Screw material</b>                           | Stainless steel AISI 304                         |
| <b>Screw type</b>                               | Torx T15 slotted head type                       |
| <b>Combustion behaviour</b>                     | V0 (UL94)  |
| <b>Tightening torque</b>                        | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)                      |
| <b>Cable clamp screw</b>                        | Tightening torque 1.5Nm (13.3 Lb-in) max.        |
| <b>Pendant fixing ring</b>                      | Stainless steel AISI 304                         |
| <b>Flexible cable gland</b>                     | M16x1.5 suitable for cable D.5÷10mm              |
| <b>Rated insulation voltage</b>                 | Ui 300V - Uimp 2.5KV (IEC-EN60947-1)             |
| <b>Protection against electric shock</b>        | Class II (IEC-EN61140)                           |
| <b>Fitted for outdoor application</b>           | yes  |
| <b>Combustion behaviour</b>                     | 960°(IEC-EN60695-2-12)                           |
| <b>Pushbutton and electrical contacts block</b> | See 020 product range: 020 SM2 D.22mm            |
| <b>Warranty period</b>                          | 18 months  |

# Technische Zeichnungen

