

Datenblatt

080RU200-GP4C

Hängetaster, Fernbedienung, 3+1 Bohrungen, gelb, UL



Merkmale

Baureihe	Hängetaster, Fernbedienung 200x83 mm
Komponenten	Mit 4 Bohrungen Ø 22
Artikel-Nr.	080RU200-GP4C
Beschreibung	Hängetaster, Fernbedienung, 3+1 Bohrungen, gelb, UL
Farbe	Giallo RAL1003 / Grigio RAL7035
Gewicht - gr	300,0
Zolltarifnummer	85381000
GTIN	8052878072353

Technische Daten

Approvals	CE, UL, CSA
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Operating temperatures	-35° ÷ +80°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK08 (IEC-EN62262)
Housing material	High impact grade thermoplastic polymer
Manufacturing process	Injection moulding
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	Torx T15 slotted head type
Combustion behaviour	V0 (UL94)
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Cable clamp screw	Tightening torque 1.5Nm (13.3 Lb-in) max.
Pendant fixing ring	Stainless steel AISI 304
Flexible cable gland	M20x1.5 suitable for cable D.6÷12mm
Rated insulation voltage	Ui 300V - Uimp 2.5KV (IEC-EN60947-1)
Protection against electric shock	Class II (IEC-EN61140)
Fitted for outdoor application	yes
Combustion behaviour	960°(IEC-EN60695-2-12)
Pushbutton and electrical contacts block	See 020 product range: 020 SM2 D.22mm
Warranty period	18 months

Technische Zeichnungen
