

## Datablad

080RU200-GP4C

Hangende drukknopkast, afstandsbediening, 3+1 gaten, geel, UL



## Kenmerken

<b>Bereik</b>	Hangende drukknopkasten, afstandsbediening 200x83 mm
<b>Component</b>	Met 4 gaten Ø 22
<b>Rubriek</b>	080RU200-GP4C
<b>Omschrijving</b>	Hangende drukknopkast, afstandsbediening, 3+1 gaten, geel, UL
<b>Kleur</b>	Giallo RAL1003 / Grigio RAL7035
<b>Gewicht</b>	300,0
<b>Douanetarief</b>	85381000
<b>GTIN</b>	8052878072353

## Technische gegevens

<b>Approvals</b>	CE, UL, CSA
<b>Compliance with standards</b>	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
<b>Operating temperatures</b>	-35° ÷ +80°C
<b>Protection degree</b>	IP66 - IP69 (IEC-EN60529)
<b>Protection against impact</b>	IK08 (IEC-EN62262)
<b>Housing material</b>	High impact grade thermoplastic polymer
<b>Manufacturing process</b>	Injection moulding
<b>Gasket material</b>	TPE thermoplastic elastomer
<b>Screw material</b>	Stainless steel AISI 304
<b>Screw type</b>	Torx T15 slotted head type
<b>Combustion behaviour</b>	V0 (UL94)
<b>Tightening torque</b>	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
<b>Cable clamp screw</b>	Tightening torque 1.5Nm (13.3 Lb-in) max.
<b>Pendant fixing ring</b>	Stainless steel AISI 304
<b>Flexible cable gland</b>	M20x1.5 suitable for cable D.6÷12mm
<b>Rated insulation voltage</b>	Ui 300V - Uimp 2.5KV (IEC-EN60947-1)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Fitted for outdoor application</b>	yes
<b>Combustion behaviour</b>	960°(IEC-EN60695-2-12)
<b>Pushbutton and electrical contacts block</b>	See 020 product range: 020 SM2 D.22mm

---

**Warranty period**

18 months

---

## Technische tekeningen

---