

Datasheet

080RU265-GP1

Pendant push-button station, remote control, 1 hole, yellow, UL



Features

| | |
|-----------------------|---|
| Range | Pendant push-button stations, remote control 265x83 mm |
| components | With 1 hole Ø 22 |
| Code | 080RU265-GP1 |
| Description | Pendant push-button station, remote control, 1 hole, yellow, UL |
| Colour | Giallo RAL1003 / Grigio RAL7035 |
| Weight - gr | 346.0 |
| Customs Tariff | 85381000 |
| GTIN | 8052878072414 |

Datasheet

| | |
|---|--|
| Approvals | CE, UL, CSA |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Operating temperatures | -35° ÷ +80°C |
| Protection degree | IP66 - IP69 (IEC-EN60529) |
| Protection against impact | IK08 (IEC-EN62262) |
| Housing material | High impact grade thermoplastic polymer |
| Manufacturing process | Injection moulding |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Screw type | Torx T15 slotted head type |
| Combustion behaviour | V0 (UL94) |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Cable clamp screw | Tightening torque 1.5Nm (13.3 Lb-in) max. |
| Pendant fixing ring | Stainless steel AISI 304 |
| Flexible cable gland | M20x1.5 suitable for cable D.6÷12mm |
| Rated insulation voltage | Ui 300V - Uimp 2.5KV (IEC-EN60947-1) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Fitted for outdoor application | yes |
| Combustion behaviour | 960°(IEC-EN60695-2-12) |
| Pushbutton and electrical contacts block | See 020 product range: 020 SM2 D.22mm |

Warranty period

18 months

Technical drawings

