

## Datablad

080T0707-6G

Druknopkast in PA + glasvezel 70x70x63, zonder gaten, geel



## Kenmerken

<b>Bereik</b>	Druknopkasten, Techno-serie 70x70
<b>Component</b>	Deksel zonder gaten
<b>Rubriek</b>	080T0707-6G
<b>Omschrijving</b>	Druknopkast in PA + glasvezel 70x70x63, zonder gaten, geel
<b>Kleur</b>	Giallo RAL1003 / Grigio RAL7035
<b>Gewicht</b>	118,0
<b>Douanetarief</b>	85381000
<b>GTIN</b>	8052878074043

## Technische gegevens

<b>Approvals</b>	CE, EAC
<b>Compliance with standards</b>	UNI EN ISO 13850, UNI EN ISO 12100, IEC-EN60947-5-5
<b>Compliance with standards</b>	IEC-ENC60947-1, IEC-EN60947-5-1
<b>Operating temperatures</b>	-35° ÷ +80°C
<b>Protection against impact</b>	IK09 (IEC-EN62262)
<b>Protection degree</b>	IP66 - IP67 - IP69 (IEC-EN60529)
<b>Enclosure material</b>	PA Polyamide - glass fiber reinforced
<b>Gasket material</b>	TPE thermoplastic elastomer
<b>Screw material</b>	Stainless steel AISI 304
<b>Screw type</b>	Torx T15 slotted head type
<b>Enclosure thickness</b>	3,5mm
<b>Tightening torque</b>	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Combustion behaviour</b>	HB (UL94)
<b>Combustion behaviour</b>	650°(IEC-EN60695-2-11)
<b>Fitted for outdoor application</b>	yes
<b>Warranty period</b>	18 months

## Technische tekeningen

