

Datenblatt

080T0707-6GC01
Drucktastergehäuse in PA + Glasfaser 70x70x63 gelb mit Not-Halt mit
Schlüsselentriegelung, 1NC



Merkmale

Baureihe	Drucktastergehäuse, Serie Techno 70x70
Komponenten	Not-Halt-Komplettgerät mit Pilztaster Schlüsselentriegelung
Artikel-Nr.	080T0707-6GC01
Beschreibung	Drucktastergehäuse in PA + Glasfaser 70x70x63 gelb mit Not-Halt mit Schlüsselentriegelung, 1NC
Farbe	Giallo RAL1003 / Grigio RAL7035 / Operatore rosso
Gewicht - gr	0,0
Zolltarifnummer	85365080
GTIN	8052878078935

Technische Daten

Approvals	CE
Compliance with standards	UNI EN ISO 13850,UNI EN ISO 12100,IEC-EN60947-5-5
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Operating temperatures	-35° ÷ +80°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK08 (IEC-EN62262)
Enclosure material	PA Polyamide - glass fiber reinforced
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	Torx T15 slotted head type
Enclosure thickness	3,5mm
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Combustion behaviour	HB (UL94)
Combustion behaviour	650°(IEC-EN60695-2-12)
Fitted for outdoor application	yes
Pushbutton characteristics	See items from family 020 / CMD&SIGN; SM2 Ø22
Warranty period	18 months

Technische Zeichnungen

