

Datenblatt

080T0707-6GF01

Drucktastergehäuse in PA + Glasfaser 70x70x63 gelb mit Not-Halt-Taster d40, 1NC



Merkmale

| | |
|------------------------|---|
| Baureihe | Drucktastergehäuse, Serie Techno 70x70 |
| Komponenten | Not-Halt-Komplettgerät mit Pilzdrucktaster D40 |
| Artikel-Nr. | 080T0707-6GF01 |
| Beschreibung | Drucktastergehäuse in PA + Glasfaser 70x70x63 gelb mit Not-Halt-Taster d40, 1NC |
| Farbe | Giallo RAL1003 / Grigio RAL7035 / Operatore rosso |
| Gewicht - gr | 172,0 |
| Zolltarifnummer | 85365080 |
| GTIN | 8052878077167 |

Technische Daten

| | |
|--|---|
| Approvals | CE |
| Compliance with standards | UNI EN ISO 13850,UNI EN ISO 12100,IEC-EN60947-5-5 |
| Compliance with standards | IEC-ENC60947-1, IEC-EN60947-5-1 |
| Operating temperatures | -35° ÷ +80°C |
| Protection against impact | IK09 (IEC-EN62262) |
| Protection degree | IP66 - IP67 - IP69 (IEC-EN60529) |
| Enclosure material | PA Polyamide - glass fiber reinforced |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Screw type | Torx T15 slotted head type |
| Enclosure thickness | 3,5mm |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Combustion behaviour | HB (UL94) |
| Combustion behaviour | 650°(IEC-EN60695-2-11) |
| Fitted for outdoor application | yes |
| Pushbutton characteristics | See items from family 020 / CMD&SIGN; SM2 Ø22 |
| Warranty period | 18 months |

Technische Zeichnungen

