

## Fiche technique

080T0707-6GP1

Boîte à boutons in PA + fibre verre 70x70x63, 1 trou d22, jaune



## Caractéristiques

|                                     |   |
|-------------------------------------|---|
| <b>Portée</b>                       | Boîtes à boutons, série Techno 70x70                            |
| <b>Composant</b>                    | Couvercle avec 1 trou D22                                       |
| <b>Code</b>                         | 080T0707-6GP1   |
| <b>Désignation des marchandises</b> | Boîte à boutons in PA + fibre verre 70x70x63, 1 trou d22, jaune |
| <b>Couleur</b>                      | Giallo RAL1003 / Grigio RAL7035                                 |
| <b>Poids</b>                        | 113,0   |
| <b>Tarif douanier</b>               | 85381000  |
| <b>GTIN</b>                         | 8052878074081   |

## Données techniques

|  |   |
|--|---|
| <b>Approvals</b>                         | CE, EAC   |
| <b>Compliance with standards</b>         | UNI EN ISO 13850, UNI EN ISO 12100, IEC-EN60947-5-5 |
| <b>Compliance with standards</b>         | IEC-ENC60947-1, IEC-EN60947-5-1                     |
| <b>Operating temperatures</b>            | -35° ÷ +80°C  |
| <b>Protection against impact</b>         | IK09 (IEC-EN62262)                                  |
| <b>Protection degree</b>                 | IP66 - IP67 - IP69 (IEC-EN60529)                    |
| <b>Enclosure material</b>                | PA Polyamide - glass fiber reinforced               |
| <b>Gasket material</b>                   | TPE thermoplastic elastomer                         |
| <b>Screw material</b>                    | Stainless steel AISI 304                            |
| <b>Screw type</b>                        | Torx T15 slotted head type                          |
| <b>Enclosure thickness</b>               | 3,5mm   |
| <b>Tightening torque</b>                 | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)                         |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                              |
| <b>Combustion behaviour</b>              | HB (UL94)   |
| <b>Combustion behaviour</b>              | 650°(IEC-EN60695-2-11)                              |
| <b>Fitted for outdoor application</b>    | yes   |
| <b>Warranty period</b>                   | 18 months   |

## Dessins techniques

