

Datablad

080T0707-6SC

Drukknopkast in PA + glasvezel met sleutelschakelaar



Kenmerken

Bereik	Drukknopkasten, Techno-serie 70x70
Component	Eenheid met sleutelschakelaar 2 posities
Rubriek	080T0707-6SC
Omschrijving	Drukknopkast in PA + glasvezel met sleutelschakelaar
Kleur	Grigio RAL7035 / Operatore nero
Gewicht	200,0
Douanetarief	85365080
GTIN	8052878078195

Technische gegevens

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Operating temperatures	-35° ÷ +80°C
Protection against impact	IK09 (IEC-EN62262)
Protection degree	IP66 - IP67 - IP69 (IEC-EN60529)
Enclosure material	PA Polyamide - glass fiber reinforced
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	Torx T15 slotted head type
Enclosure thickness	3,5mm
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Combustion behaviour	HB (UL94)
Combustion behaviour	650°(IEC-EN60695-2-11)
Fitted for outdoor application	yes
Pushbutton characteristics	See items from family 020 / CMD&SIGN; SM2 Ø22
Warranty period	18 months

Technische tekeningen

