

## Scheda Dati

080T0707-6SM

Scatola pulsantiera in poliammide rinforzato 70x70x63 con selettore a manopola 2 posizioni



## Caratteristiche

|                         |   |
|-------------------------|---|
| <b>Gamma</b>            | Scatole pulsantiere serie Techno 70x70 mm                 |
| <b>Componente</b>       | Completa con selettore a manopola 2 posizioni             |
| <b>Codice</b>           | 080T0707-6SM  |
| <b>Descrizione</b>      | Scatola pulsantiera in poliammide rinforzato 70x70x63 con |
| <b>Colore</b>           | Grigio RAL7035 / Operatore nero                           |
| <b>Peso</b>             | 200,0   |
| <b>Tariffa doganale</b> | 85365080  |
| <b>GTIN</b>             | 8052878078171   |

## Dati tecnici

|  |   |
|--|---|
| <b>Approvals</b>                         | CE  |
| <b>Compliance with standards</b>         | IEC-ENC60947-1, IEC-EN60947-5-1               |
| <b>Operating temperatures</b>            | -35° ÷ +80°C                                  |
| <b>Protection against impact</b>         | IK09 (IEC-EN62262)                            |
| <b>Protection degree</b>                 | IP66 - IP67 - IP69 (IEC-EN60529)              |
| <b>Enclosure material</b>                | PA Polyamide - glass fiber reinforced         |
| <b>Gasket material</b>                   | TPE thermoplastic elastomer                   |
| <b>Screw material</b>                    | Stainless steel AISI 304                      |
| <b>Screw type</b>                        | Torx T15 slotted head type                    |
| <b>Enclosure thickness</b>               | 3,5mm   |
| <b>Tightening torque</b>                 | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)                   |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                        |
| <b>Combustion behaviour</b>              | HB (UL94)                                     |
| <b>Combustion behaviour</b>              | 650°(IEC-EN60695-2-11)                        |
| <b>Fitted for outdoor application</b>    | yes   |
| <b>Pushbutton characteristics</b>        | See items from family 020 / CMD&SIGN; SM2 Ø22 |
| <b>Warranty period</b>                   | 18 months                                     |

## Disegni tecnici

