

Fiche technique

080T0709-6GP2L

Boîte à boutons in PA + fibre verre 70x90x63, 2 trous d22, jaune



Caractéristiques

| | |
|-------------------------------------|--|
| Portée | Boîtes à boutons, série Techno 70x90 |
| Composant | Couvercle avec 2 trous D22 |
| Code | 080T0709-6GP2L |
| Désignation des marchandises | Boîte à boutons in PA + fibre verre 70x90x63, 2 trous d22, jaune |
| Couleur | Giallo RAL1003 / Grigio RAL7035 |
| Poids | 132,0 |
| Tarif douanier | 85381000 |
| GTIN | 8052878074210 |

Données techniques

| | |
|--|---|
| Approvals | CE, EAC |
| Compliance with standards | UNI EN ISO 13850, UNI EN ISO 12100, IEC-EN60947-5-5 |
| Compliance with standards | IEC-ENC60947-1, IEC-EN60947-5-1 |
| Operating temperatures | -35° ÷ +80°C |
| Protection against impact | IK09 (IEC-EN62262) |
| Protection degree | IP66 - IP67 - IP69 (IEC-EN60529) |
| Enclosure material | PA Polyamide - glass fiber reinforced |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Screw type | Torx T15 slotted head type |
| Enclosure thickness | 3,5mm |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Combustion behaviour | HB (UL94) |
| Combustion behaviour | 650°(IEC-EN60695-2-11) |
| Fitted for outdoor application | yes |
| Warranty period | 18 months |

Dessins techniques

