

Hoja de datos

080T0709-6P1

Caja pulsadora in PA + fibra de vidrio 70x90x63, 1 orificio d22



Características

| | |
|-------------------------|---|
| Rango | Cajas pulsadoras, serie Techno 70x90 |
| Componente | Tapa con 1 orificio D22 |
| Código | 080T0709-6P1 |
| Descripción | Caja pulsadora in PA + fibra de vidrio 70x90x63, 1 orificio d22 |
| Color | Grigio RAL7016 / Grigio RAL7035 |
| Peso | 132,0 |
| Arancel aduanero | 85381000 |
| GTIN | 8052878074159 |

Datos técnicos

| | |
|--|---|
| Approvals | CE, EAC |
| Compliance with standards | UNI EN ISO 13850,UNI EN ISO 12100,IEC-EN60947-5-5 |
| Compliance with standards | IEC-ENC60947-1, IEC-EN60947-5-1 |
| Operating temperatures | -35° ÷ +80°C |
| Protection against impact | IK09 (IEC-EN62262) |
| Protection degree | IP66 - IP67 - IP69 (IEC-EN60529) |
| Enclosure material | PA Polyamide - glass fiber reinforced |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Screw type | Torx T15 slotted head type |
| Enclosure thickness | 3,5mm |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Combustion behaviour | HB (UL94) |
| Combustion behaviour | 650°(IEC-EN60695-2-11) |
| Fitted for outdoor application | yes |
| Warranty period | 18 months |

Dibujos técnicos

