

Datablad

080T0709-6P2L

Druknopkast in PA + glasvezel 70x90x63, 2 gaten d22



Kenmerken

Bereik	Druknopkasten, Techno-serie 70x90
Component	Deksel met 2 gaten D22
Rubriek	080T0709-6P2L
Omschrijving	Druknopkast in PA + glasvezel 70x90x63, 2 gaten d22
Kleur	Grigio RAL7016 / Grigio RAL7035
Gewicht	132,0
Douanetarief	85381000
GTIN	8052878074197

Technische gegevens

Approvals	CE, EAC
Compliance with standards	UNI EN ISO 13850,UNI EN ISO 12100,IEC-EN60947-5-5
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Operating temperatures	-35° ÷ +80°C
Protection against impact	IK09 (IEC-EN62262)
Protection degree	IP66 - IP67 - IP69 (IEC-EN60529)
Enclosure material	PA Polyamide - glass fiber reinforced
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	Torx T15 slotted head type
Enclosure thickness	3,5mm
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Combustion behaviour	HB (UL94)
Combustion behaviour	650°(IEC-EN60695-2-11)
Fitted for outdoor application	yes
Warranty period	18 months

Technische tekeningen

