# Datasheet

080T0709-6S47
Push-button box in PA + glass fibre 70x90x63 with 2 guarded black push-buttons, arrows



## Features

| | |
|---|---|
| **Range** | Push-button boxes, Techno series 70x90 |
| **components** | Unit with 2 push-buttons arrow symbols |
| **Code** | 080T0709-6S47 |
| **Description** | Push-button box in PA + glass fibre 70x90x63 with 2 guarded black push-buttons, arrows |
| **Colour** | Grigio RAL7016 / RAL7035 / Operatori nero-nero |
| **Weight - gr** | 200.0 |
| **Customs Tariff** | 85365080 |
| **GTIN** | 8052878078232 |

## Datasheet

| | |
|---|---|
| **Approvals** | CE |
| **Compliance with standards** | IEC-ENC60947-1, IEC-EN60947-5-1 |
| **Operating temperatures** | -35° ÷ +80°C |
| **Protection degree** | IP66 - IP69 (IEC-EN60529) |
| **Protection against impact** | IK08 (IEC-EN62262) |
| **Enclosure material** | PA Polyamide - glass fiber reinforced |
| **Gasket material** | TPE thermoplastic elastomer |
| **Screw material** | Stainless steel AISI 304 |
| **Screw type** | Torx T15 slotted head type |
| **Enclosure thickness** | 3,5mm |
| **Tightening torque** | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| **Protection against electric shock** | Class II (IEC-EN61140) |
| **Combustion behaviour** | HB (UL94) |
| **Combustion behaviour** | 650°(IEC-EN60695-2-12) |
| **Fitted for outdoor application** | yes |
| **Pushbutton characteristics** | See items from family 020 / CMD&SIGN; SM2 Ø22 |
| **Warranty period** | 18 months |

## Technical drawings




