

Scheda Dati

080T0714-6G

Scatola pulsantiera in poliammide rinforzato 70x140x63, senza fori, giallo



Caratteristiche

| | |
|-------------------------|---|
| Gamma | Scatole pulsantiera serie Techno 70x140 mm |
| Componente | Coperchio senza fori |
| Codice | 080T0714-6G |
| Descrizione | Scatola pulsantiera in poliammide rinforzato 70x140x63, |
| Colore | Giallo RAL1003 / Grigio RAL7035 |
| Peso | 182,0 |
| Tariffa doganale | 85381000 |
| GTIN | 8052878074258 |

Dati tecnici

| | |
|--|---|
| Approvals | CE, EAC |
| Compliance with standards | UNI EN ISO 13850, UNI EN ISO 12100, IEC-EN60947-5-5 |
| Compliance with standards | IEC-ENC60947-1, IEC-EN60947-5-1 |
| Operating temperatures | -35° ÷ +80°C |
| Protection against impact | IK09 (IEC-EN62262) |
| Protection degree | IP66 - IP67 - IP69 (IEC-EN60529) |
| Enclosure material | PA Polyamide - glass fiber reinforced |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Screw type | Torx T15 slotted head type |
| Enclosure thickness | 3,5mm |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Combustion behaviour | HB (UL94) |
| Combustion behaviour | 650°(IEC-EN60695-2-11) |
| Fitted for outdoor application | yes |
| Warranty period | 18 months |

Disegni tecnici

