# Scheda Dati

080T0714-6P2
Scatola pulsantiera in poliammide rinforzato 70x140x63, 2 fori d22



## Caratteristiche

| | |
|---|---|
| **Gamma** | Scatole pulsantiere serie Techno 70x140 mm |
| **Componente** | Coperchio con 2 fori D22 |
| **Codice** | 080T0714-6P2 |
| **Descrizione** | Scatola pulsantiera in poliammide rinforzato 70x140x63, 2 |
| **Colore** | Grigio RAL7016 / Grigio RAL7035 |
| **Peso** | 182,0 |
| **Tariffa doganale** | 85381000 |
| **GTIN** | 8052878074272 |

## Dati tecnici

| | |
|---|---|
| **Approvals** | CE, EAC |
| **Compliance with standards** | IEC-EN62208 |
| **Operating temperatures** | -35° ÷ +80°C |
| **Protection against impact** | IK08 (IEC-EN62262) |
| **Protection degree** | IP66 - IP67 - IP69 (IEC-EN60529) |
| **Enclosure material** | PA Polyamide - glass fiber reinforced |
| **Gasket material** | TPE thermoplastic elastomer |
| **Screw material** | Stainless steel AISI 304 |
| **Screw type** | Torx T15 slotted head type |
| **Enclosure thickness** | 3,5mm |
| **Tightening torque** | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| **Protection against electric shock** | Class II (IEC-EN61140) |
| **Heavy metal-free** | yes |
| **PVC-free** | yes |
| **Silicon-free** | yes |
| **Combustion behaviour** | HB (UL94) |
| **Combustion behaviour** | 650°(IEC-EN60695-2-12) |
| **Fitted for outdoor application** | yes |
| **Warranty period** | 18 months |

## Disegni tecnici

