

## Scheda Dati

080T0714-6P2

Scatola pulsantiera in poliammide rinforzato 70x140x63, 2 fori d22



## Caratteristiche

|                         |   |
|-------------------------|---|
| <b>Gamma</b>            | Scatole pulsantiera serie Techno 70x140 mm                |
| <b>Componente</b>       | Coperchio con 2 fori D22                                  |
| <b>Codice</b>           | 080T0714-6P2  |
| <b>Descrizione</b>      | Scatola pulsantiera in poliammide rinforzato 70x140x63, 2 |
| <b>Colore</b>           | Grigio RAL7016 / Grigio RAL7035                           |
| <b>Peso</b>             | 182,0   |
| <b>Tariffa doganale</b> | 85381000  |
| <b>GTIN</b>             | 8052878074272   |

## Dati tecnici

|  |   |
|--|---|
| <b>Approvals</b>                         | CE, EAC   |
| <b>Compliance with standards</b>         | UNI EN ISO 13850, UNI EN ISO 12100, IEC-EN60947-5-5 |
| <b>Compliance with standards</b>         | IEC-ENC60947-1, IEC-EN60947-5-1                     |
| <b>Operating temperatures</b>            | -35° ÷ +80°C  |
| <b>Protection against impact</b>         | IK09 (IEC-EN62262)                                  |
| <b>Protection degree</b>                 | IP66 - IP67 - IP69 (IEC-EN60529)                    |
| <b>Enclosure material</b>                | PA Polyamide - glass fiber reinforced               |
| <b>Gasket material</b>                   | TPE thermoplastic elastomer                         |
| <b>Screw material</b>                    | Stainless steel AISI 304                            |
| <b>Screw type</b>                        | Torx T15 slotted head type                          |
| <b>Enclosure thickness</b>               | 3,5mm   |
| <b>Tightening torque</b>                 | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)                         |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                              |
| <b>Combustion behaviour</b>              | HB (UL94)   |
| <b>Combustion behaviour</b>              | 650°(IEC-EN60695-2-11)                              |
| <b>Fitted for outdoor application</b>    | yes   |
| <b>Warranty period</b>                   | 18 months   |

## Disegni tecnici

