


## Hoja de datos

080T0718-6P5L

Caja pulsadora in PA + fibra de vidrio 70x180x63, 5 orificios d22



## Características

|                         |   |
|-------------------------|---|
| <b>Rango</b>            | Cajas pulsadoras, serie Techno 70x180                             |
| <b>Componente</b>       | Tapa con 5 orificios D22  |
| <b>Código</b>           | 080T0718-6P5L   |
| <b>Descripción</b>      | Caja pulsadora in PA + fibra de vidrio 70x180x63, 5 orificios d22 |
| <b>Color</b>            | Grigio RAL7016 / Grigio RAL7035                                   |
| <b>Peso</b>             | 222,0   |
| <b>Arancel aduanero</b> | 85381000  |
| <b>GTIN</b>             | 8052878074395   |

## Datos técnicos

|  |   |
|--|---|
| <b>Approvals</b>                         | CE, EAC   |
| <b>Compliance with standards</b>         | UNI EN ISO 13850,UNI EN ISO 12100,IEC-EN60947-5-5 |
| <b>Compliance with standards</b>         | IEC-ENC60947-1, IEC-EN60947-5-1                   |
| <b>Operating temperatures</b>            | -35° ÷ +80°C                                      |
| <b>Protection against impact</b>         | IK09 (IEC-EN62262)                                |
| <b>Protection degree</b>                 | IP66 - IP67 - IP69 (IEC-EN60529)                  |
| <b>Enclosure material</b>                | PA Polyamide - glass fiber reinforced             |
| <b>Gasket material</b>                   | TPE thermoplastic elastomer                       |
| <b>Screw material</b>                    | Stainless steel AISI 304                          |
| <b>Screw type</b>                        | Torx T15 slotted head type                        |
| <b>Enclosure thickness</b>               | 3,5mm   |
| <b>Tightening torque</b>                 | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)                       |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                            |
| <b>Combustion behaviour</b>              | HB (UL94)   |
| <b>Combustion behaviour</b>              | 650°(IEC-EN60695-2-11)                            |
| <b>Fitted for outdoor application</b>    | yes   |
| <b>Warranty period</b>                   | 18 months   |

## Dibujos técnicos

