

## Hoja de datos

080T0727-6P6L

Caja pulsadora in PA + fibra de vidrio 70x267x63, 6 orificios d22



## Características

<b>Rango</b>	Cajas pulsadoras, serie Techno 70x267
<b>Componente</b>	Tapa con 6 orificios D22
<b>Código</b>	080T0727-6P6L
<b>Descripción</b>	Caja pulsadora in PA + fibra de vidrio 70x267x63, 6 orificios d22
<b>Color</b>	Grigio RAL7016 / Grigio RAL7035
<b>Peso</b>	315,0
<b>Arancel aduanero</b>	85381000
<b>GTIN</b>	8052878074494

## Datos técnicos

<b>Approvals</b>	CE, EAC
<b>Compliance with standards</b>	UNI EN ISO 13850,UNI EN ISO 12100,IEC-EN60947-5-5
<b>Compliance with standards</b>	IEC-ENC60947-1, IEC-EN60947-5-1
<b>Operating temperatures</b>	-35° ÷ +80°C
<b>Protection against impact</b>	IK09 (IEC-EN62262)
<b>Protection degree</b>	IP66 - IP67 - IP69 (IEC-EN60529)
<b>Enclosure material</b>	PA Polyamide - glass fiber reinforced
<b>Gasket material</b>	TPE thermoplastic elastomer
<b>Screw material</b>	Stainless steel AISI 304
<b>Screw type</b>	Torx T15 slotted head type
<b>Enclosure thickness</b>	3,5mm
<b>Tightening torque</b>	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Combustion behaviour</b>	HB (UL94)
<b>Combustion behaviour</b>	650°(IEC-EN60695-2-11)
<b>Fitted for outdoor application</b>	yes
<b>Warranty period</b>	18 months

## Dibujos técnicos

