

Datablad

080T0727-6P6LC

Drukknopkast in PA + glasvezel 70x267x63, 6 gaten d22



Kenmerken

| | |
|---------------------|---|
| Bereik | Drukknopkasten, Techno-serie 70x267 |
| Component | Deksel met 6 gaten D22 |
| Rubriek | 080T0727-6P6LC |
| Omschrijving | Drukknopkast in PA + glasvezel 70x267x63, 6 gaten d22 |
| Kleur | Grigio RAL7016 / Grigio RAL7035 |
| Gewicht | 315,0 |
| Douanetarief | 85381000 |
| GTIN | 8052878075897 |

Technische gegevens

| | |
|--|---|
| Approvals | CE, EAC |
| Compliance with standards | UNI EN ISO 13850,UNI EN ISO 12100,IEC-EN60947-5-5 |
| Compliance with standards | IEC-ENC60947-1, IEC-EN60947-5-1 |
| Operating temperatures | -35° ÷ +80°C |
| Protection against impact | IK09 (IEC-EN62262) |
| Protection degree | IP66 - IP67 - IP69 (IEC-EN60529) |
| Enclosure material | PA Polyamide - glass fiber reinforced |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Screw type | Torx T15 slotted head type |
| Enclosure thickness | 3,5mm |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Combustion behaviour | HB (UL94) |
| Combustion behaviour | 650°(IEC-EN60695-2-11) |
| Fitted for outdoor application | yes |
| Warranty period | 18 months |

Technische tekeningen

