

## Datasheet

080T0909-7

Push-button box in PA + glass fibre 90x90x74, undrilled



## Features

|                       |   |
|-----------------------|---|
| <b>Range</b>          | Push-button boxes, Techno series 90x90                  |
| <b>components</b>     | Undrilled cover   |
| <b>Code</b>           | 080T0909-7  |
| <b>Description</b>    | Push-button box in PA + glass fibre 90x90x74, undrilled |
| <b>Colour</b>         | Grigio RAL7016 / Grigio RAL7035                         |
| <b>Weight - gr</b>    | 226.0   |
| <b>Customs Tariff</b> | 85381000  |
| <b>GTIN</b>           | 8052878071516   |

## Datasheet

|  |                                       |
|--|---------------------------------------|
| <b>Approvals</b>                         | CE, EAC                               |
| <b>Compliance with standards</b>         | IEC-EN62208                           |
| <b>Operating temperatures</b>            | -35° ÷ +80°C                          |
| <b>Protection degree</b>                 | IP67 - IP69 (IEC-EN60529)             |
| <b>Protection against impact</b>         | IK09 (IEC-EN62262)                    |
| <b>Enclosure material</b>                | PA Polyamide - glass fiber reinforced |
| <b>Gasket material</b>                   | TPE thermoplastic elastomer           |
| <b>Screw material</b>                    | Stainless steel AISI 304              |
| <b>Screw type</b>                        | HEX 3 slotted head - M4 thread        |
| <b>Threaded bushing material</b>         | Brass OT58 - M4 thread                |
| <b>Enclosure thickness</b>               | 3,5mm                                 |
| <b>Tightening torque</b>                 | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)           |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                |
| <b>Halogen-free</b>                      | yes                                   |
| <b>Combustion behaviour</b>              | HB (UL94)                             |
| <b>Combustion behaviour</b>              | 650°(IEC-EN60695-2-11)                |
| <b>Fitted for outdoor application</b>    | yes                                   |
| <b>Warranty period</b>                   | 18 months                             |

## Technical drawings

---

