

Datablad

080T0918-7G

Druknopkast in PA + glasvezel 90x180x74, zonder gaten, geel



Kenmerken

| | |
|---------------------|---|
| Bereik | Druknopkasten, Techno-serie 90x180 |
| Component | Deksel zonder gaten |
| Rubriek | 080T0918-7G |
| Omschrijving | Druknopkast in PA + glasvezel 90x180x74, zonder gaten, geel |
| Kleur | Giallo RAL1003 / Grigio RAL7035 |
| Gewicht | 388,0 |
| Douanetarief | 85381000 |
| GTIN | 8052878074777 |

Technische gegevens

| | |
|--|---------------------------------------|
| Approvals | CE, EAC |
| Compliance with standards | IEC-EN62208 |
| Operating temperatures | -35° ÷ +80°C |
| Protection degree | IP67 - IP69 (IEC-EN60529) |
| Protection against impact | IK09 (IEC-EN62262) |
| Enclosure material | PA Polyamide - glass fiber reinforced |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Screw type | HEX 3 slotted head - M4 thread |
| Threaded bushing material | Brass OT58 - M4 thread |
| Enclosure thickness | 3,5mm |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Halogen-free | yes |
| Combustion behaviour | HB (UL94) |
| Combustion behaviour | 650°(IEC-EN60695-2-11) |
| Fitted for outdoor application | yes |
| Warranty period | 18 months |

Technische tekeningen

