

Hoja de datos

080T0927-7G

Caja pulsadora in PA + fibra de vidrio 90x267x74, sin orificios, amarillo



Características

| | |
|-------------------------|---------------------------------------------------------------------------|
| Rango | Cajas pulsadoras, serie Techno 90x267 |
| Componente | Tapa sin orificios |
| Código | 080T0927-7G |
| Descripción | Caja pulsadora in PA + fibra de vidrio 90x267x74, sin orificios, amarillo |
| Color | Giallo RAL1003 / Grigio RAL7035 |
| Peso | 530,0 |
| Arancel aduanero | 85381000 |
| GTIN | 8052878074814 |

Datos técnicos

| | |
|------------------------------------------|---------------------------------------|
| Approvals | CE, EAC |
| Compliance with standards | IEC-EN62208 |
| Operating temperatures | -35° ÷ +80°C |
| Protection degree | IP67 - IP69 (IEC-EN60529) |
| Protection against impact | IK09 (IEC-EN62262) |
| Enclosure material | PA Polyamide - glass fiber reinforced |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Screw type | HEX 3 slotted head - M4 thread |
| Threaded bushing material | Brass OT58 - M4 thread |
| Enclosure thickness | 3,5mm |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Halogen-free | yes |
| Combustion behaviour | HB (UL94) |
| Combustion behaviour | 650°(IEC-EN60695-2-11) |
| Fitted for outdoor application | yes |
| Warranty period | 18 months |

Dibujos técnicos

