

## Scheda Dati

080T0927-7P9M  
Scatola pulsantiera in poliammide rinforzato 90x267x74, 9 fori d22



## Caratteristiche

|                  |                                                           |
|------------------|-----------------------------------------------------------|
| Gamma            | Scatole pulsantiere serie Techno 90x267 mm                |
| Componente       | Coperchio con 9 fori D22                                  |
| Codice           | 080T0927-7P9M                                             |
| Descrizione      | Scatola pulsantiera in poliammide rinforzato 90x267x74, 9 |
| Colore           | Grigio RAL7016 / Grigio RAL7035                           |
| Peso             | 503,0                                                     |
| Tariffa doganale | 85381000                                                  |
| GTIN             | 8052878078096                                             |

## Dati tecnici

|                                   |                                       |
|-----------------------------------|---------------------------------------|
| Approvals                         | CE, EAC                               |
| Compliance with standards         | IEC-EN62208                           |
| Operating temperatures            | -35° ÷ +80°C                          |
| Protection against impact         | IK08 (IEC-EN62262)                    |
| Protection degree                 | IP66 - IP67 - IP69 (IEC-EN60529)      |
| Enclosure material                | PA Polyamide - glass fiber reinforced |
| Gasket material                   | TPE thermoplastic elastomer           |
| Screw material                    | Stainless steel AISI 304              |
| Screw type                        | HEX 3 slotted head - M4 thread        |
| Threaded bushing material         | Brass OT58 - M4 thread                |
| Enclosure thickness               | 3,5mm                                 |
| Tightening torque                 | 0.8 ÷ 1.2 Nm (7.1 ÷ 10.6 Lb-in)       |
| Protection against electric shock | Class II (IEC-EN61140)                |
| Heavy metal-free                  | yes                                   |
| PVC-free                          | yes                                   |
| Silicon-free                      | yes                                   |
| Halogen-free                      | yes                                   |
| Combustion behaviour              | HB (UL94)                             |
| Combustion behaviour              | 650°(IEC-EN60695-2-12)                |
| Fitted for outdoor application    | yes                                   |
| Warranty period                   | 18 months                             |

# Disegni tecnici

