

# Datablad

080T0927-9P7

Drukknopkast in PA + glasvezel 90x267x94, 7 gaten d22



## Kenmerken

|              |                                                       |
|--------------|-------------------------------------------------------|
| Bereik       | Drukknopkasten, Techno-serie 90x267                   |
| Component    | Deksel met 7 gaten D22                                |
| Rubriek      | 080T0927-9P7                                          |
| Omschrijving | Drukknopkast in PA + glasvezel 90x267x94, 7 gaten d22 |
| Kleur        | Grigio RAL7016 / Grigio RAL7035                       |
| Gewicht      | 0,0                                                   |
| Douanetarief | 85381000                                              |
| GTIN         | 8052878080518                                         |

## Technische gegevens

|                                   |                                       |
|-----------------------------------|---------------------------------------|
| Approvals                         | CE, EAC                               |
| Compliance with standards         | IEC-EN62208                           |
| Operating temperatures            | -35° ÷ +80°C                          |
| Protection against impact         | IK08 (IEC-EN62262)                    |
| Protection degree                 | IP66 - IP67 - IP69 (IEC-EN60529)      |
| Enclosure material                | PA Polyamide - glass fiber reinforced |
| Gasket material                   | TPE thermoplastic elastomer           |
| Screw material                    | Stainless steel AISI 304              |
| Screw type                        | HEX 3 slotted head - M4 thread        |
| Threaded bushing material         | Brass OT58 - M4 thread                |
| Enclosure thickness               | 3,5mm                                 |
| Tightening torque                 | 0.8 ÷ 1.2 Nm (7.1 ÷ 10.6 Lb-in)       |
| Protection against electric shock | Class II (IEC-EN61140)                |
| Heavy metal-free                  | yes                                   |
| PVC-free                          | yes                                   |
| Silicon-free                      | yes                                   |
| Halogen-free                      | yes                                   |
| Combustion behaviour              | HB (UL94)                             |
| Combustion behaviour              | 650°(IEC-EN60695-2-12)                |
| Fitted for outdoor application    | yes                                   |
| Warranty period                   | 18 months                             |

# Technische tekeningen

