

Datenblatt

080T1818-7P9C

Drucktastergehäuse in PA + Glasfaser 180x180x74, 9 Bohrungen d22



Merkmale

| | |
|------------------------|--|
| Baureihe | Drucktastergehäuse, Serie Techno 180x180 |
| Komponenten | Deckel mit 9 Bohrungen D22 |
| Artikel-Nr. | 080T1818-7P9C |
| Beschreibung | Drucktastergehäuse in PA + Glasfaser 180x180x74, 9 Bohrungen d22 |
| Farbe | Grigio RAL7016 / Grigio RAL7035 |
| Gewicht - gr | 564,0 |
| Zolltarifnummer | 85381000 |
| GTIN | 8052878076993 |

Technische Daten

| | |
|--|---------------------------------------|
| Approvals | CE, EAC |
| Compliance with standards | IEC-EN62208 |
| Operating temperatures | -35° ÷ +80°C |
| Protection degree | IP67 - IP69 (IEC-EN60529) |
| Protection against impact | IK09 (IEC-EN62262) |
| Enclosure material | PA Polyamide - glass fiber reinforced |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Screw type | HEX 3 slotted head - M4 thread |
| Threaded bushing material | Brass OT58 - M4 thread |
| Enclosure thickness | 3,5mm |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Halogen-free | yes |
| Combustion behaviour | HB (UL94) |
| Combustion behaviour | 650°(IEC-EN60695-2-11) |
| Fitted for outdoor application | yes |
| Warranty period | 18 months |

Technische Zeichnungen

