


## Datablad

080T1818-9T

Drukknopkast in PA + glasvezel 180x180x94, zonder gaten, transparant



## Kenmerken

|                     |  |
|---------------------|--|
| <b>Bereik</b>       | Drukknopkasten, Techno-serie 180x180                                 |
| <b>Component</b>    | Deksel zonder gaten  |
| <b>Rubriek</b>      | 080T1818-9T  |
| <b>Omschrijving</b> | Drukknopkast in PA + glasvezel 180x180x94, zonder gaten, transparant |
| <b>Kleur</b>        | Trasparente / Grigio RAL7035   |
| <b>Gewicht</b>      | 564,0  |
| <b>Douanetarief</b> | 85381000   |
| <b>GTIN</b>         | 8052878076399  |

## Technische gegevens

|  |                                       |
|--|---------------------------------------|
| <b>Approvals</b>                         | CE, EAC                               |
| <b>Compliance with standards</b>         | IEC-EN62208                           |
| <b>Operating temperatures</b>            | -35° ÷ +80°C                          |
| <b>Protection degree</b>                 | IP67 - IP69 (IEC-EN60529)             |
| <b>Protection against impact</b>         | IK09 (IEC-EN62262)                    |
| <b>Enclosure material</b>                | PA Polyamide - glass fiber reinforced |
| <b>Gasket material</b>                   | TPE thermoplastic elastomer           |
| <b>Screw material</b>                    | Stainless steel AISI 304              |
| <b>Screw type</b>                        | HEX 3 slotted head - M4 thread        |
| <b>Threaded bushing material</b>         | Brass OT58 - M4 thread                |
| <b>Enclosure thickness</b>               | 3,5mm                                 |
| <b>Tightening torque</b>                 | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)           |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                |
| <b>Halogen-free</b>                      | yes                                   |
| <b>Combustion behaviour</b>              | HB (UL94)                             |
| <b>Combustion behaviour</b>              | 650°(IEC-EN60695-2-11)                |
| <b>Fitted for outdoor application</b>    | yes                                   |
| <b>Warranty period</b>                   | 18 months                             |

## Technische tekeningen

