
# Datasheet

080T1827-7P13C
Push-button box in PA + glass fibre 180x267x74, 13 holes d22



## Features

| | |
|---|---|
| **Range** | Push-button boxes, Techno series 180x267 |
| **components** | Cover with 13 holes D22 |
| **Code** | 080T1827-7P13C |
| **Description** | Push-button box in PA + glass fibre 180x267x74, 13 holes d22 |
| **Colour** | Grigio RAL7016 / Grigio RAL7035 |
| **Weight - gr** | 564.0 |
| **Customs Tariff** | 85381000 |
| **GTIN** | 8052878076702 |

## Datasheet

| | |
|---|---|
| **Approvals** | CE, EAC |
| **Compliance with standards** | IEC-EN62208 |
| **Operating temperatures** | -35° ÷ +80°C |
| **Protection against impact** | IK08 (IEC-EN62262) |
| **Protection degree** | IP66 - IP67 - IP69 (IEC-EN60529) |
| **Enclosure material** | PA Polyamide - glass fiber reinforced |
| **Gasket material** | TPE thermoplastic elastomer |
| **Screw material** | Stainless steel AISI 304 |
| **Screw type** | HEX 3 slotted head - M4 thread |
| **Threaded bushing material** | Brass OT58 - M4 thread |
| **Enclosure thickness** | 3,5mm |
| **Tightening torque** | 0.8 ÷ 1.2 Nm (7.1 ÷ 10.6 Lb-in) |
| **Protection against electric shock** | Class II (IEC-EN61140) |
| **Heavy metal-free** | yes |
| **PVC-free** | yes |
| **Silicon-free** | yes |
| **Halogen-free** | yes |
| **Combustion behaviour** | HB (UL94) |
| **Combustion behaviour** | 650°(IEC-EN60695-2-12) |
| **Fitted for outdoor application** | yes |

| | |
|---|---|
| **Warranty period** | 18 months |

## Technical drawings

