

## Datenblatt

080TEU0918-7P5C

Drucktastergehäuse in PA + Glasfaser 90x180x74, 5 Bohrungen d22, UL, Ergonomischer Deckel



## Merkmale

|                 |                                                                                           |
|-----------------|-------------------------------------------------------------------------------------------|
| Baureihe        | Drucktastergehäuse, Serie Techno 90x180 Ergo                                              |
| Komponenten     | Deckel mit 5 Bohrungen D22                                                                |
| Artikel-Nr.     | 080TEU0918-7P5C                                                                           |
| Beschreibung    | Drucktastergehäuse in PA + Glasfaser 90x180x74, 5 Bohrungen d22, UL, Ergonomischer Deckel |
| Farbe           | Grigio RAL7016 / Grigio RAL7035                                                           |
| Gewicht - gr    | 0,0                                                                                       |
| Zolltarifnummer | 85381000                                                                                  |
| GTIN            | 8052878080389                                                                             |

## Technische Daten

|                                   |                                                    |
|-----------------------------------|----------------------------------------------------|
| Approvals                         | CE, UL, CSA, EAC                                   |
| Compliance with standards         | IEC-EN62208, UL508, CSA C22.2 No.14-13             |
| Operating temperatures            | -35° ÷ +80°C                                       |
| Protection against impact         | IK08 (IEC-EN62262)                                 |
| Protection degree                 | IP66-IP67-IP69 -TYPE 4,4X (IEC-EN60529 - NEMA 250) |
| Enclosure material                | PA Polyamide - glass fiber reinforced              |
| Gasket material                   | TPE thermoplastic elastomer                        |
| Screw material                    | Stainless steel AISI 304                           |
| Screw type                        | HEX 3 slotted head - M4 thread                     |
| Threaded bushing material         | Stainless steel AISI 304 - M4 thread               |
| Enclosure thickness               | 3,5mm                                              |
| Tightening torque                 | 0.8 ÷ 1.2 Nm (7.1 ÷ 10.6 Lb-in)                    |
| Protection against electric shock | Class II (IEC-EN61140)                             |
| Heavy metal-free                  | yes                                                |
| PVC-free                          | yes                                                |
| Silicon-free                      | yes                                                |
| Halogen-free                      | yes                                                |
| Combustion behaviour              | 960°(IEC-EN60695-2-12)                             |
| Fitted for outdoor application    | yes                                                |

|                      |            |
|----------------------|------------|
| Combustion behaviour | 5VA (UL94) |
| Warranty period      | 18 months  |

# Technische Zeichnungen

