

Hoja de datos

080TU0707-6GA01

Caja pulsadora in PA + fibra de vidrio 70x70x63 amarillo con Pulsador de emergencia d32, 1NC, conforme a normas UL



Características

| | |
|-------------------------|--|
| Rango | Cajas pulsadoras, serie Techno 70x70 |
| Componente | Unidad de emergencia con pulsador seta D32 |
| Código | 080TU0707-6GA01 |
| Descripción | Caja pulsadora in PA + fibra de vidrio 70x70x63 amarillo con Pulsador de emergencia d32, 1NC, conforme a normas UL |
| Peso | 0,0 |
| Arancel aduanero | 85365080 |
| GTIN | 8052878078904 |

Datos técnicos

| | |
|--|--|
| Approvals | CE |
| Compliance with standards | UNI EN ISO 13850,UNI EN ISO 12100,IEC-EN60947-5-5 |
| Compliance with standards | IEC-ENC60947-1, IEC-EN60947-5-1 |
| Operating temperatures | -35° ÷ +80°C |
| Protection against impact | IK09 (IEC-EN62262) |
| Protection degree | IP66-IP67-IP69 -TYPE 4,4X (IEC-EN60529 - NEMA 250) |
| Enclosure material | PA Polyamide - glass fiber reinforced |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Screw type | Torx T15 slotted head type |
| Enclosure thickness | 3,5mm |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Combustion behaviour | 5VA (UL50 - UL746C) |
| Combustion behaviour | 960°(IEC-EN60695-2-11) |
| Combustion behaviour | V0 (UL94) |
| Fitted for outdoor application | yes |
| Pushbutton characteristics | See items from family 020 / CMD&SIGN; SM2 Ø22 |
| Warranty period | 18 months |

Dibujos técnicos

