

Datenblatt

080TU0707-6GA12

Drucktastergehäuse in PA + Glasfaser 70x70x63 gelb mit Not-Halt-Taster d32, 1NO+2NC, konform mit UL-Normen



Merkmale

Baureihe	Drucktastergehäuse, Serie Techno 70x70
Komponenten	Not-Halt-Komplettgerät mit Pilzdrucktaster D32
Artikel-Nr.	080TU0707-6GA12
Beschreibung	Drucktastergehäuse in PA + Glasfaser 70x70x63 gelb mit Not-Halt-Taster d32, 1NO+2NC, konform mit UL-Normen
Gewicht - gr	0,0
Zolltarifnummer	85365080
GTIN	8052878078911

Technische Daten

Approvals	CE
Compliance with standards	UNI EN ISO 13850,UNI EN ISO 12100,IEC-EN60947-5-5
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Operating temperatures	-35° ÷ +80°C
Protection against impact	IK09 (IEC-EN62262)
Protection degree	IP66-IP67-IP69 -TYPE 4,4X (IEC-EN60529 - NEMA 250)
Enclosure material	PA Polyamide - glass fiber reinforced
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	Torx T15 slotted head type
Enclosure thickness	3,5mm
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Combustion behaviour	5VA (UL50 - UL746C)
Combustion behaviour	960°(IEC-EN60695-2-11)
Combustion behaviour	V0 (UL94)
Fitted for outdoor application	yes
Pushbutton characteristics	See items from family 020 / CMD&SIGN; SM2 Ø22
Warranty period	18 months

Technische Zeichnungen

