

Hoja de datos

080TU0707-6GC01

Caja pulsadora in PA + fibra de vidrio 70x70x63 amarillo con Pulsador de emergencia con desbloqueo por llave, 1NC, UL



Características

Rango	Cajas pulsadoras, serie Techno 70x70
Componente	Unidad de emergencia con pulsador seta con llave
Código	080TU0707-6GC01
Descripción	Caja pulsadora in PA + fibra de vidrio 70x70x63 amarillo con Pulsador de emergencia con desbloqueo por llave, 1NC, UL
Peso	0,0
Arancel aduanero	85365080
GTIN	8052878078942

Datos técnicos

Approvals	CE
Compliance with standards	UNI EN ISO 13850,UNI EN ISO 12100,IEC-EN60947-5-5
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Operating temperatures	-35° ÷ +80°C
Protection against impact	IK09 (IEC-EN62262)
Protection degree	IP66-IP67-IP69 -TYPE 4,4X (IEC-EN60529 - NEMA 250)
Enclosure material	PA Polyamide - glass fiber reinforced
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	Torx T15 slotted head type
Enclosure thickness	3,5mm
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Combustion behaviour	5VA (UL50 - UL746C)
Combustion behaviour	960°(IEC-EN60695-2-11)
Combustion behaviour	V0 (UL94)
Fitted for outdoor application	yes
Pushbutton characteristics	See items from family 020 / CMD&SIGN; SM2 Ø22
Warranty period	18 months

Dibujos técnicos

