

## Datasheet

080TU0707-6GC12

Push-button box in PA + glass fibre 70x70x63 yellow with key-release emergency push-button, 1NO+2NC, UL compliant



## Features

<b>Range</b>	Push-button boxes, Techno series 70x70
<b>components</b>	Emergency unit with key-release mushroom push-button
<b>Code</b>	080TU0707-6GC12
<b>Description</b>	Push-button box in PA + glass fibre 70x70x63 yellow with key-release emergency push-button, 1NO+2NC, UL compliant
<b>Weight - gr</b>	0.0
<b>Customs Tariff</b>	85365080
<b>GTIN</b>	8052878079000

## Datasheet

<b>Approvals</b>	CE
<b>Compliance with standards</b>	UNI EN ISO 13850,UNI EN ISO 12100,IEC-EN60947-5-5
<b>Compliance with standards</b>	IEC-ENC60947-1, IEC-EN60947-5-1
<b>Operating temperatures</b>	-35° ÷ +80°C
<b>Protection against impact</b>	IK09 (IEC-EN62262)
<b>Protection degree</b>	IP66-IP67-IP69 -TYPE 4,4X (IEC-EN60529 - NEMA 250)
<b>Enclosure material</b>	PA Polyamide - glass fiber reinforced
<b>Gasket material</b>	TPE thermoplastic elastomer
<b>Screw material</b>	Stainless steel AISI 304
<b>Screw type</b>	Torx T15 slotted head type
<b>Enclosure thickness</b>	3,5mm
<b>Tightening torque</b>	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Combustion behaviour</b>	5VA (UL50 - UL746C)
<b>Combustion behaviour</b>	960°(IEC-EN60695-2-11)
<b>Combustion behaviour</b>	V0 (UL94)
<b>Fitted for outdoor application</b>	yes
<b>Pushbutton characteristics</b>	See items from family 020 / CMD&SIGN; SM2 Ø22
<b>Warranty period</b>	18 months

## Technical drawings

