

## Datenblatt

080TU0707-6GF01

Drucktastergehäuse in PA + Glasfaser 70x70x63 gelb mit Not-Halt-Taster d40, 1NC, konform mit UL-Normen



## Merkmale

<b>Baureihe</b>	Drucktastergehäuse, Serie Techno 70x70
<b>Komponenten</b>	Not-Halt-Komplettgerät mit Pilzdrucktaster D40
<b>Artikel-Nr.</b>	080TU0707-6GF01
<b>Beschreibung</b>	Drucktastergehäuse in PA + Glasfaser 70x70x63 gelb mit Not-Halt-Taster d40, 1NC, konform mit UL-Normen
<b>Gewicht - gr</b>	172,0
<b>Zolltarifnummer</b>	85365080
<b>GTIN</b>	8052878077181

## Technische Daten

<b>Approvals</b>	CE
<b>Compliance with standards</b>	UNI EN ISO 13850,UNI EN ISO 12100,IEC-EN60947-5-5
<b>Compliance with standards</b>	IEC-ENC60947-1, IEC-EN60947-5-1
<b>Operating temperatures</b>	-35° ÷ +80°C
<b>Protection against impact</b>	IK09 (IEC-EN62262)
<b>Protection degree</b>	IP66-IP67-IP69 -TYPE 4,4X (IEC-EN60529 - NEMA 250)
<b>Enclosure material</b>	PA Polyamide - glass fiber reinforced
<b>Gasket material</b>	TPE thermoplastic elastomer
<b>Screw material</b>	Stainless steel AISI 304
<b>Screw type</b>	Torx T15 slotted head type
<b>Enclosure thickness</b>	3,5mm
<b>Tightening torque</b>	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Combustion behaviour</b>	5VA (UL50 - UL746C)
<b>Combustion behaviour</b>	960°(IEC-EN60695-2-11)
<b>Combustion behaviour</b>	V0 (UL94)
<b>Fitted for outdoor application</b>	yes
<b>Pushbutton characteristics</b>	See items from family 020 / CMD&SIGN; SM2 Ø22
<b>Warranty period</b>	18 months

## Technische Zeichnungen

