

Datablad

080TU0707-6GF01

Drukknopkast in PA + glasvezel 70x70x63 geel met Noodstopknop d40, 1NC, conform UL-normen



Kenmerken

Bereik	Drukknopkasten, Techno-serie 70x70
Component	Noodunit met paddestoeldrukknop D40
Rubriek	080TU0707-6GF01
Omschrijving	Drukknopkast in PA + glasvezel 70x70x63 geel met Noodstopknop d40, 1NC, conform UL-normen
Gewicht	172,0
Douanetarief	85365080
GTIN	8052878077181

Technische gegevens

Approvals	CE
Compliance with standards	UNI EN ISO 13850,UNI EN ISO 12100,IEC-EN60947-5-5
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Operating temperatures	-35° ÷ +80°C
Protection against impact	IK09 (IEC-EN62262)
Protection degree	IP66-IP67-IP69 -TYPE 4,4X (IEC-EN60529 - NEMA 250)
Enclosure material	PA Polyamide - glass fiber reinforced
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	Torx T15 slotted head type
Enclosure thickness	3,5mm
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Combustion behaviour	5VA (UL50 - UL746C)
Combustion behaviour	960°(IEC-EN60695-2-11)
Combustion behaviour	V0 (UL94)
Fitted for outdoor application	yes
Pushbutton characteristics	See items from family 020 / CMD&SIGN; SM2 Ø22
Warranty period	18 months

Technische tekeningen

