Datasheet

080TU0707-6GF12

Push-button box in PA + glass fibre 70x70x63 yellow with emergency push-button d40, 1NO+2NC, UL standards compliant



Features

Range	Push-button boxes, Techno series 70x70
components	Emergency unit with mushroom push-button D40
Code	080TU0707-6GF12
Description	Push-button box in PA + glass fibre 70x70x63 yellow with emergency push-button d40, 1NO+2NC, UL standards compliant
Weight - gr	200.0
Customs Tariff	85365080
GTIN	8052878077198

Datasheet

Approvals	CE
Compliance with standards	UNI EN ISO 13850,UNI EN ISO 12100,IEC-EN60947-5-5
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Operating temperatures	-35° ÷ +80°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK08 (IEC-EN62262)
Enclosure material	PA Polyamide - glass fiber reinforced
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	Torx T15 slotted head type
Enclosure thickness	3,5mm
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Halogen-free	yes
Combustion behaviour	960°(IEC-EN60695-2-12)
Combustion behaviour	V0 (UL94)
Fitted for outdoor application	yes
Pushbutton characteristics	See items from family 020 / CMD&SIGN; SM2 Ø22
Warranty period	18 months

Technical drawings



