

Datenblatt

080TU0707-6GS1

Drucktastergehäuse in PA + Glasfaser 70x70x63, 1 Bohrung d22, gelb, UL



Merkmale

Baureihe	Drucktastergehäuse, Serie Techno 70x70
Komponenten	Deckel mit 1 Bohrung D30
Artikel-Nr.	080TU0707-6GS1
Beschreibung	Drucktastergehäuse in PA + Glasfaser 70x70x63, 1 Bohrung d22, gelb, UL
Farbe	Giallo RAL1003 / Grigio RAL7035
Gewicht - gr	113,0
Zolltarifnummer	85381000
GTIN	8052878072384

Technische Daten

Approvals	CE, UL, CSA, EAC
Compliance with standards	IEC-EN62208, UL508, CSA C22.2 No.14-13
Operating temperatures	-35° ÷ +80°C
Protection against impact	IK09 (IEC-EN62262)
Protection degree	IP66-IP67-IP69 -TYPE 4,4X (IEC-EN60529 - NEMA 250)
Enclosure material	PA Polyamide - glass fiber reinforced
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	Torx T15 slotted head type
Enclosure thickness	3,5mm
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Combustion behaviour	5VA (UL50 - UL746C)
Combustion behaviour	960°(IEC-EN60695-2-11)
Combustion behaviour	V0 (UL94)
Fitted for outdoor application	yes
Warranty period	18 months

Technische Zeichnungen

