

## Datasheet

080TU0707-6P1

Push-button box in PA + glass fibre 70x70x63, 1 hole d22, UL



## Features

|                       |  |
|-----------------------|--|
| <b>Range</b>          | Push-button boxes, Techno series 70x70                       |
| <b>components</b>     | Cover with 1 holes D22                                       |
| <b>Code</b>           | 080TU0707-6P1  |
| <b>Description</b>    | Push-button box in PA + glass fibre 70x70x63, 1 hole d22, UL |
| <b>Colour</b>         | Grigio RAL7016 / Grigio RAL7035                              |
| <b>Weight - gr</b>    | 113.0  |
| <b>Customs Tariff</b> | 85381000   |
| <b>GTIN</b>           | 8052878074074  |

## Datasheet

|  |  |
|--|--|
| <b>Approvals</b>                         | CE, UL, CSA, EAC                                   |
| <b>Compliance with standards</b>         | IEC-EN62208, UL508, CSA C22.2 No.14-13             |
| <b>Operating temperatures</b>            | -35° ÷ +80°C                                       |
| <b>Protection against impact</b>         | IK09 (IEC-EN62262)                                 |
| <b>Protection degree</b>                 | IP66-IP67-IP69 -TYPE 4,4X (IEC-EN60529 - NEMA 250) |
| <b>Enclosure material</b>                | PA Polyamide - glass fiber reinforced              |
| <b>Gasket material</b>                   | TPE thermoplastic elastomer                        |
| <b>Screw material</b>                    | Stainless steel AISI 304                           |
| <b>Screw type</b>                        | Torx T15 slotted head type                         |
| <b>Enclosure thickness</b>               | 3,5mm  |
| <b>Tightening torque</b>                 | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)                        |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                             |
| <b>Combustion behaviour</b>              | 5VA (UL50 - UL746C)                                |
| <b>Combustion behaviour</b>              | 960°(IEC-EN60695-2-11)                             |
| <b>Combustion behaviour</b>              | V0 (UL94)  |
| <b>Fitted for outdoor application</b>    | yes  |
| <b>Warranty period</b>                   | 18 months  |

## Technical drawings

