

## Fiche technique

080TU0707-6PV

Boîte à boutons in PA + fibre verre 70x70x63 avec bouton affleurant, vert, UL



## Caractéristiques

<b>Portée</b>	Boîtes à boutons, série Techno 70x70
<b>Composant</b>	Complet avec bouton protégé, vert
<b>Code</b>	080TU0707-6PV
<b>Désignation des marchandises</b>	Boîte à boutons in PA + fibre verre 70x70x63 avec bouton affleurant, vert, UL
<b>Couleur</b>	Grigio RAL7016 / RAL7035 / Operatore verde
<b>Poids</b>	113,0
<b>Tarif douanier</b>	85381000
<b>GTIN</b>	8052878078157

## Données techniques

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-EN62208, UL508, CSA C22.2 No.14-13
<b>Compliance with standards</b>	IEC-ENC60947-1, IEC-EN60947-5-1
<b>Operating temperatures</b>	-35° ÷ +80°C
<b>Protection against impact</b>	IK09 (IEC-EN62262)
<b>Protection degree</b>	IP66-IP67-IP69 -TYPE 4,4X (IEC-EN60529 - NEMA 250)
<b>Enclosure material</b>	PA Polyamide - glass fiber reinforced
<b>Gasket material</b>	TPE thermoplastic elastomer
<b>Screw material</b>	Stainless steel AISI 304
<b>Screw type</b>	Torx T15 slotted head type
<b>Enclosure thickness</b>	3,5mm
<b>Tightening torque</b>	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Combustion behaviour</b>	5VA (UL50 - UL746C)
<b>Combustion behaviour</b>	960°(IEC-EN60695-2-11)
<b>Combustion behaviour</b>	V0 (UL94)
<b>Fitted for outdoor application</b>	yes
<b>Pushbutton characteristics</b>	See items from family 020 / CMD&SIGN; SM2 Ø22
<b>Warranty period</b>	18 months

## Dessins techniques

