

Datablad

080TU0707-6PV

Drukknopkast in PA + glasvezel 70x70x63 met Druknop met bescherming, groen, conform UL-normen



Kenmerken

| | |
|---------------------|---|
| Bereik | Drukknopkasten, Techno-serie 70x70 |
| Component | Eenheid met groene drukknoop met afscherming |
| Rubriek | 080TU0707-6PV |
| Omschrijving | Drukknopkast in PA + glasvezel 70x70x63 met Druknop met bescherming, groen, conform UL-normen |
| Kleur | Grigio RAL7016 / RAL7035 / Operatore verde |
| Gewicht | 113,0 |
| Douanetarief | 85381000 |
| GTIN | 8052878078157 |

Technische gegevens

| | |
|--|--|
| Approvals | CE |
| Compliance with standards | IEC-EN62208, UL508, CSA C22.2 No.14-13 |
| Compliance with standards | IEC-ENC60947-1, IEC-EN60947-5-1 |
| Operating temperatures | -35° ÷ +80°C |
| Protection against impact | IK09 (IEC-EN62262) |
| Protection degree | IP66-IP67-IP69 -TYPE 4,4X (IEC-EN60529 - NEMA 250) |
| Enclosure material | PA Polyamide - glass fiber reinforced |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Screw type | Torx T15 slotted head type |
| Enclosure thickness | 3,5mm |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Combustion behaviour | 5VA (UL50 - UL746C) |
| Combustion behaviour | 960°(IEC-EN60695-2-11) |
| Combustion behaviour | V0 (UL94) |
| Fitted for outdoor application | yes |
| Pushbutton characteristics | See items from family 020 / CMD&SIGN; SM2 Ø22 |
| Warranty period | 18 months |

Technische tekeningen

