


Datasheet

080TU0707-6T

Push-button box in PA + glass fibre 70x70x63, undrilled, clear lid, UL



Features

| | |
|-----------------------|--|
| Range | Push-button boxes, Techno series 70x70 |
| components | Undrilled cover |
| Code | 080TU0707-6T |
| Description | Push-button box in PA + glass fibre 70x70x63, undrilled, clear lid, UL |
| Colour | Trasparente / Grigio RAL7035 |
| Weight - gr | 113.0 |
| Customs Tariff | 85381000 |
| GTIN | 8052878075545 |

Datasheet

| | |
|--|--|
| Approvals | CE, UL, CSA, EAC |
| Compliance with standards | IEC-EN62208, UL508, CSA C22.2 No.14-13 |
| Operating temperatures | -35° ÷ +80°C |
| Protection against impact | IK09 (IEC-EN62262) |
| Protection degree | IP66-IP67-IP69 -TYPE 4,4X (IEC-EN60529 - NEMA 250) |
| Lid material | PC Polycarbonate |
| Enclosure material | PA Polyamide - glass fiber reinforced |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Screw type | Torx T15 slotted head type |
| Enclosure thickness | 3,5mm |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Combustion behaviour | 5VA (UL50 - UL746C) |
| Combustion behaviour | V-2 (UL94) |
| Combustion behaviour | 960°(IEC-EN60695-2-11) |
| Fitted for outdoor application | yes |
| Warranty period | 18 months |

Technical drawings

