

Fiche technique

080TU0709-6G

Boîte à boutons in PA + fibre verre 70x90x63, sans trous, jaune, UL



Caractéristiques

| | |
|-------------------------------------|---|
| Portée | Boîtes à boutons, série Techno 70x90 |
| Composant | Couvercle sans trous |
| Code | 080TU0709-6G |
| Désignation des marchandises | Boîte à boutons in PA + fibre verre 70x90x63, sans trous, jaune, UL |
| Couleur | Giallo RAL1003 / Grigio RAL7035 |
| Poids | 132,0 |
| Tarif douanier | 85381000 |
| GTIN | 8052878074142 |

Données techniques

| | |
|--|--|
| Approvals | CE, UL, CSA, EAC |
| Compliance with standards | IEC-EN62208, UL508, CSA C22.2 No.14-13 |
| Operating temperatures | -35° ÷ +80°C |
| Protection against impact | IK09 (IEC-EN62262) |
| Protection degree | IP66-IP67-IP69 -TYPE 4,4X (IEC-EN60529 - NEMA 250) |
| Enclosure material | PA Polyamide - glass fiber reinforced |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Screw type | Torx T15 slotted head type |
| Enclosure thickness | 3,5mm |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Combustion behaviour | 5VA (UL50 - UL746C) |
| Combustion behaviour | 960°(IEC-EN60695-2-11) |
| Combustion behaviour | V0 (UL94) |
| Fitted for outdoor application | yes |
| Warranty period | 18 months |

Dessins techniques

