# Datenblatt

080TU0709-6GP1
Drucktastergehäuse in PA + Glasfaser 70x90x63, 1 Bohrung d22, gelb, UL



## Merkmale

| | |
|---|---|
| **Baureihe** | Drucktastergehäuse, Serie Techno 70x90 |
| **Komponenten** | Deckel mit 1 Bohrungen D22 |
| **Artikel-Nr.** | 080TU0709-6GP1 |
| **Beschreibung** | Drucktastergehäuse in PA + Glasfaser 70x90x63, 1 Bohrung d22, gelb, UL |
| **Farbe** | Giallo RAL1003 / Grigio RAL7035 |
| **Gewicht - gr** | 132,0 |
| **Zolltarifnummer** | 85381000 |
| **GTIN** | 8052878074180 |

## Technische Daten

| | |
|---|---|
| **Approvals** | CE, UL, CSA, EAC |
| **Compliance with standards** | IEC-EN62208, UL508, CSA C22.2 No.14-13 |
| **Operating temperatures** | -35° ÷ +80°C |
| **Protection against impact** | IK08 (IEC-EN62262) |
| **Protection degree** | IP66-IP67-IP69 -TYPE 4,4X (IEC-EN60529 - NEMA 250) |
| **Enclosure material** | PA Polyamide - glass fiber reinforced |
| **Gasket material** | TPE thermoplastic elastomer |
| **Screw material** | Stainless steel AISI 304 |
| **Screw type** | Torx T15 slotted head type |
| **Enclosure thickness** | 3,5mm |
| **Tightening torque** | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| **Protection against electric shock** | Class II (IEC-EN61140) |
| **Heavy metal-free** | yes |
| **PVC-free** | yes |
| **Silicon-free** | yes |
| **Halogen-free** | yes |
| **Combustion behaviour** | 960°(IEC-EN60695-2-12) |
| **Fitted for outdoor application** | yes |
| **Combustion behaviour** | 5VA (UL94) |
| **Warranty period** | 18 months |

## Technische Zeichnungen

