

## Scheda Dati

080TU0709-6GP2L

Scatola pulsantiera in poliammide rinforzato 70x90x63, 2 fori d22, giallo, UL



## Caratteristiche

|                         |  |
|-------------------------|--|
| <b>Gamma</b>            | Scatole pulsantiera serie Techno 70x90 mm                |
| <b>Componente</b>       | Coperchio con 2 fori D22                                 |
| <b>Codice</b>           | 080TU0709-6GP2L  |
| <b>Descrizione</b>      | Scatola pulsantiera in poliammide rinforzato 70x90x63, 2 |
| <b>Colore</b>           | Giallo RAL1003 / Grigio RAL7035                          |
| <b>Peso</b>             | 132,0  |
| <b>Tariffa doganale</b> | 85381000   |
| <b>GTIN</b>             | 8052878074227  |

## Dati tecnici

|  |  |
|--|--|
| <b>Approvals</b>                         | CE, UL, CSA, EAC                                   |
| <b>Compliance with standards</b>         | IEC-EN62208, UL508, CSA C22.2 No.14-13             |
| <b>Operating temperatures</b>            | -35° ÷ +80°C                                       |
| <b>Protection against impact</b>         | IK09 (IEC-EN62262)                                 |
| <b>Protection degree</b>                 | IP66-IP67-IP69 -TYPE 4,4X (IEC-EN60529 - NEMA 250) |
| <b>Enclosure material</b>                | PA Polyamide - glass fiber reinforced              |
| <b>Gasket material</b>                   | TPE thermoplastic elastomer                        |
| <b>Screw material</b>                    | Stainless steel AISI 304                           |
| <b>Screw type</b>                        | Torx T15 slotted head type                         |
| <b>Enclosure thickness</b>               | 3,5mm  |
| <b>Tightening torque</b>                 | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)                        |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                             |
| <b>Combustion behaviour</b>              | 5VA (UL50 - UL746C)                                |
| <b>Combustion behaviour</b>              | 960°(IEC-EN60695-2-11)                             |
| <b>Combustion behaviour</b>              | V0 (UL94)  |
| <b>Fitted for outdoor application</b>    | yes  |
| <b>Warranty period</b>                   | 18 months  |

## Disegni tecnici

