

Scheda Dati

080TU0709-6PE

Scatola pulsantiera in poliammide rinforzato 70x90x63 giallo con pulsante emergenza D40 e pulsante, UL



Caratteristiche

Gamma	Scatole pulsantiere serie Techno 70x90 mm
Componente	Completa d'emergenza con fungo D40 e pulsante
Codice	080TU0709-6PE
Descrizione	Scatola pulsantiera in poliammide rinforzato 70x90x63
Colore	Giallo RAL1003 / Grigio RAL7035
Peso	200,0
Tariffa doganale	85365080
GTIN	8052878078997

Dati tecnici

Approvals	CE
Compliance with standards	UNI EN ISO 13850,UNI EN ISO 12100,IEC-EN60947-5-5
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Operating temperatures	-35° ÷ +80°C
Protection against impact	IK09 (IEC-EN62262)
Protection degree	IP66-IP67-IP69 -TYPE 4,4X (IEC-EN60529 - NEMA 250)
Enclosure material	PA Polyamide - glass fiber reinforced
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	Torx T15 slotted head type
Enclosure thickness	3,5mm
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Combustion behaviour	5VA (UL50 - UL746C)
Combustion behaviour	960°(IEC-EN60695-2-11)
Combustion behaviour	V0 (UL94)
Fitted for outdoor application	yes
Pushbutton characteristics	See items from family 020 / CMD&SIGN; SM2 Ø22
Warranty period	18 months

Disegni tecnici

